







The Timer & Counter Company H. Kuhnke Ltd

Unit 6 Focus 303
Focus Way, Walworth Business Park
Andover, Hampshire
SP10 5NY, United Kingdom

Telephone: +44 (0)1264 364194 Facsimile: +44 (0)1264 365991 Email: sales@kuhnke.co.uk

Pneumatic Totalising Counter - 50.660

- 6 digit display
- Manual/pneumatic reset
- Simple installation
- M5 ports
- Maintenance free operation
- Light & durable

Display	6 digit
Digit Height	4mm
Operating Pressure	2-8 bar
Air Quality	Oil free and dry, 5 micron filtered
Mechanical Life	30 x 10 ⁶
Protection Class	IP40
Operating Temperature	0+60°C
Connection	M5 female threaded ports
Mounting Position	Base mounting
Count input	Adding
Pulse Length Min	8ms minimum
Count Frequency max	25Hz
Pulse duty factor	The non pulse period must be long enough to allow pressure to drop to approx. 0.15 bar for a minimum of 12ms to ouput 2
Reset	Manual with button or pneumatic reset minimum pulse length 180ms Please Note: minimum time period between last count pulse and pneumatic reset is 50ms
PART NUMBERS	

Kuhnke pneumatic totalising counters display a total count of pneumatic pulses.

Function: On application of an air pressure impulse to port(Z) the value 1 is added to the digital read out. Reset functions include a manual push button and a port (Y) for reset by pneumatic pulse.

6 digit totalising counter

Alternative Products

50.660

See panel mount versions 50.670 and 8 digit non-resettable 50.650

Disclaimer: The information shown in this document is for guidance only. No liability is accepted for any errors or omissions. The designer or user is solely responsible for the safe and proper application of the parts, assemblies or equipment supplied.